

# 1412E(4647E)/1414E(4655E)

Complies with ISO/CE/ANSI/AS/CU-TR/KCS standards

## Product Highlights

### Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions

### Reduced maintenance costs

- Exclusive open chassis design reduces daily maintenance costs
- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

### More reliable performance

- New wide scissor design, for a more stable working-at-height experience
- Bumper rail and indented sliding groove designed for anti-scratch

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

# SINOBOOM

Sinoboom Intelligent Equipment Co Ltd

📍 No.128 East Jinzhou Av., Ningxiang Hi-Tech Industry Park,  
Changsha, Hunan, China, 410600

🌐 [www.sinoboom.com](http://www.sinoboom.com)

✉ [sales@sinoboom.com](mailto:sales@sinoboom.com)

# 1412E(4647E)/1414E(4655E)

Complies with ISO/CE/ANSI/AS/CU-TR/KCS standards

Model		1412E(4647E)		1414E(4655E)	
Dimensions		Metric	US	Metric	US
Max Working Height		15.8m	51'10"	15.8m	51'10"
A Max Platform Height		13.8m	45'3"	13.8m	45'3"
B Max Horizontal Extension		0.9m	3'	0.9m	3'
C Length-Stowed		2.78m	9'	2.78m	9'
D Width-Stowed		1.27m	4'2"	1.41m	4'7"
Height-stowed	Rail Folded	1.96m	6'5"	1.96m	6'5"
	E Rail Unfolded	2.6m	8'6"	2.6m	8'6"
F Wheelbase		2.22m	7'3"	2.22m	7'3"
Ground Clearance(Pothole Guard Stowed)		0.1m	4"	0.1m	4"
Ground Clearance(Pothole Guard Deployed)		25mm	0.98"	25mm	0.98"
Platform Dimensions(L×W×H)		2.64m×1.15m×1.1m (8'8"×3'9"×3'7")		2.64m×1.15m×1.1m (8'8"×3'9"×3'7")	
<b>Performance</b>					
Platform Allowable Occupants(Indoor/ Outdoor)		2 persons/-		2 persons/1 person	
Platform Capacity		227kg	500lbs	227kg	500lbs
Drive Speed-Stowed		4km/h	2.5mph	4km/h	2.5mph
Drive Speed-Raised		0.8km/h	0.5mph	0.8km/h	0.5mph
Elevation Time(Unloaded)		75s~85s		75s~85s	
Descent Time(Unloaded)		55s~63s		55s~63s	
Gradeability		25%		25%	
Turning Radius(Inside/Outside)		0/2.64m	0/8'8"	0/2.64m	0/8'8"
Tilt Rating(Front to Back/Side to Side)		3°/1.5°		3°/1.5°	
Tyres-solid		380×125mm	15×5"	380×125mm	15×5"
<b>Power</b>					
Batteries		12V×4/300Ah		12V×4/300Ah	
Power Source		24V DC		24V DC	
Drive Mode		Motor, front-wheel		Motor, front-wheel	
Charger Input		100~240V AC		100~240V AC	
Charger Output		30A		30A	
Hydraulic System Capacity		41L	9gal	41L	9gal
<b>Weight</b>					
Weight		3,375kg	7,442lbs	3,430kg	7,563lbs
Standards Compliance		ISO/CE/ANSI/CSA/AS/CU-TR/KCS			

